


### Properties

|                    |  |
|--------------------|--|
| <b>Properties</b>  | flame retardant and not self-extinguishing, complies with DIN VDE 0278 |
| <b>Colour</b>      | black  |
| <b>Temp. min.</b>  | -55 °C   |
| <b>Temp. max.</b>  | 110 °C   |
| <b>Temp. range</b> | Min. shrinking temperature of 110 °C                                   |
| <b>Material</b>    | crosslinked modified polyolefin  |



### Description

Shrink hose usable in the widest possible range of applications, flame-retardant with interior adhesive coating for better bonding.

### Additional information

Provides additional protection against climatic influences (e.g. swage fittings for use near sea water) or used for cable bundling

### Item

| Identification | Internal Ø<br>(mm) | Wall thickness<br>(mm) | Min. shrinkage Ø<br>(mm) | Shrinking rate |
|----------------|--------------------|------------------------|--------------------------|----------------|
| SSTK 2006      | 20                 | 2                      | 6,0                      | to 3,5:1       |
| SSTK 3010      | 30                 | 2                      | 10,0                     | to 3,5:1       |
| SSTK 4012      | 40                 | 2                      | 12,0                     | to 3,5:1       |
| SSTK 5018      | 54                 | 2                      | 18,0                     | to 3,5:1       |