

STOP ROV

Stopflex mounting, pipe fitting

Properties

Application	Personal protection against whipping hose
Material	Steel



Description

A high tensile steel cable with lug and hooks fitted.

Ordering information

Please order the appropriate STOP-FS clamp separately.

Additional information

The steel cable is anchored with an appropriate STOP-FS clamp on the hose and at a fixed point. This prevents the hose from whipping around.

Item

Identification	Mounting hole (mm)	Length (mm)	Bore (mm)
STOP ROV 145 L 300	14,5	300	6,4
STOP ROV 170 L 300	17,0	300	6,4
STOP ROV 185 L 300	18,5	300	6,4
STOP ROV 205 L 300	20,5	300	6,4
STOP ROV 225 L 300	22,5	300	6,4
STOP ROV 245 L 300	24,5	300	6,4
STOP ROV 265 L 300	26,5	300	6,4
STOP ROV 305 L 300	30,5	300	6,4
STOP ROV 340 L 450	34,0	450	8,4
STOP ROV 365 L 450	36,5	450	8,4
STOP ROV 425 L 450	42,5	450	8,4
STOP ROV 455 L 450	45,5	450	8,4
STOP ROV 490 L 450	49,0	450	8,4
STOP ROV 525 L 450	52,5	450	8,4
STOP ROV 600 L 450	60,0	450	8,4