

## Properties

|                    |  |
|--------------------|--|
| <b>Application</b> | Personal protection against oil jet injuries |
| <b>Inner layer</b> | special nylon                                |
| <b>Colour</b>      | black  |
| <b>Temp. max.</b>  | 100 °C                                       |



## Note

Extremely abrasion resistant, flame retardant.

## Description

Interweaved nylon threads with maximum tensile strength atomise the hazardous oil jet that emerges when a hose bursts.

## Item

| Identification | Internal Ø<br>(mm) |
|----------------|--------------------|
| TGF ISO 17     | 17                 |
| TGF ISO 20     | 20                 |
| TGF ISO 23     | 23                 |
| TGF ISO 25     | 25                 |
| TGF ISO 27     | 27                 |
| TGF ISO 31     | 31                 |
| TGF ISO 33     | 33                 |
| TGF ISO 36     | 36                 |
| TGF ISO 40     | 40                 |
| TGF ISO 44     | 44                 |
| TGF ISO 47     | 47                 |
| TGF ISO 53     | 53                 |
| TGF ISO 55     | 55                 |
| TGF ISO 60     | 60                 |
| TGF ISO 66     | 66                 |
| TGF ISO 73     | 73                 |
| TGF ISO 93     | 93                 |
| TGF ISO 112    | 112                |
| TGF ISO 127    | 127                |