

Properties				
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.			
Connection 1	UN/UNF external threads			
Sealing form 1	74° outer cone			
Residual pressure:	Coupling under residual pressure is possible			
Material	Steel			
Surface	electro galvanised			



Description

Screw couplings are designed for high pressures and pressure pulses. It is recommended to combine only couplings same manufacturer.

Additional information

If fitted correctly, the screw sleeve completely covers the brake ring.

The self-locking thread prevents unwanted loosening due to vibrations.

The robust construction makes them ideal for use in harsh conditions.

Item								
Identification	Size	DN*	Connecting thread	Coupling thread	Operating pressure	Mineral oil temp. min.	Mineral oil temp. max.	SF coup.*
					(bar)	(°C)	(°C)	
SKF 10 HJ 2	2	10	UNF 9/16" -18	Rd. 28 x 2	350,0	-25	100	4
SKF 13 HJ 2	2	12	UNF 3/4" -16	Rd. 28 x 2	350,0	-25	100	4

BD = Working pressure - SF gek. = Safety factor coupled

Accessories	
SKF ZUBS	Dust pro- tect- ion for SKF
SKF ZUBS AL	Cap

Spare parts		
SKF BREMSRING	Brake ring for screw coupling	
SKF STUETZRING	Support ring for SKF	
SKF ORING	O-ring for SKF	