SKF IN SP

Screwed coupling fixed half

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	NPT internal thread
Sealing form 1	thread seal
Residual pressure:	Coupling under residual pressure is possible
compatible with	Pioneer
Additional feature	with ball valve
Material	High resistance special steel
Surface	galvanised, white chromised



Description

Screw couplings are designed for high pressures and pressure pulses.

Ordering information

Other pressure and temperature figures available on request.

Additional information

The robust construction makes them ideal for use in harsh conditions.

Item

Identification	Size	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKF 06 IN SP	1	6	NPT 1/4" -18	700,0	3	-25	125
SKF 10 IN 06 SP	2	10	NPT 1/4" -18	700,0	3	-25	125
SKF 10 IN SP	2	10	NPT 3/8" -18	700,0	3	-30	80

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKF ZUBS SP	Dust protection for SKF...SP

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.