

SKFS HL / SKFS HS

Screw coupling (fixed)

Properties

| | |
|---------------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Design | Coupling with bulkhead connection |
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | 24° inner cone |
| Residual pressure: | Coupling under residual pressure is possible |
| Material | Steel |
| Surface | electro galvanised |



Description

Screw couplings are designed for high pressures and pressure pulses. It is recommended to combine only couplings same manufacturer.

Ordering information

Other pressure and temperature figures available on request.

Additional information

If fitted correctly, the screw sleeve completely covers the brake ring. The self-locking thread prevents unwanted loosening due to vibrations. The robust construction makes them ideal for use in harsh conditions.

Item

| Identification | Size | DN* | Series | for external pipe Ø (mm) | Connecting thread | Coupling thread | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) | SF coup.* |
|----------------|------|-----|--------|--------------------------|-------------------|-----------------|--------------------------|-----------------------------|-----------------------------|-----------|
| SKFS 04 HL 1 | 1 | 4 | L | 6 | M 12x1,5 | Rd. 24 x 2 | 315,0 | -25 | 100 | 4 |
| SKFS 06 HL 1 | 1 | 6 | L | 8 | M 14x1,5 | Rd. 24 x 2 | 315,0 | -30 | 100 | 4 |
| SKFS 06 HL 2 | 2 | 6 | L | 8 | M 14x1,5 | Rd. 28 x 2 | 315,0 | -30 | 100 | 4 |
| SKFS 06 HL 3 | 3 | 6 | L | 8 | M 14x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 08 HL 2 | 2 | 8 | L | 10 | M 16x1,5 | Rd. 28 x 2 | 315,0 | -30 | 100 | 4 |
| SKFS 08 HL 3 | 3 | 8 | L | 10 | M 16x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 10 HL 3 | 3 | 10 | L | 12 | M 18x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 10 HL 4 | 4 | 10 | L | 12 | M 18x1,5 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 13 HL 3 | 3 | 12 | L | 15 | M 22x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 13 HL 4 | 4 | 12 | L | 15 | M 22x1,5 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 16 HL 3 | 3 | 16 | L | 18 | M 26x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 16 HL 4 | 4 | 16 | L | 18 | M 26x1,5 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 16 HL 5 | 5 | 16 | L | 18 | M 26x1,5 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 20 HL 5 | 5 | 19 | L | 22 | M 30x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 25 HL 5 | 5 | 25 | L | 28 | M 36x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 32 HL 6 | 6 | 31 | L | 35 | M 45x2 | Rd. 70 x 3 | 160,0 | -25 | 100 | 4 |
| SKFS 40 HL 6 | 6 | 38 | L | 42 | M 52x2 | Rd. 70 x 3 | 160,0 | -25 | 100 | 4 |
| SKFS 04 HS 1 | 1 | 4 | S | 8 | M 16x1,5 | Rd. 24 x 2 | 400,0 | -25 | 100 | 4 |
| SKFS 06 HS 2 | 2 | 6 | S | 10 | M 18x1,5 | Rd. 28 x 2 | 325,0 | -30 | 100 | 4 |
| SKFS 06 HS 3 | 3 | 6 | S | 10 | M 18x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 08 HS 2 | 2 | 8 | S | 12 | M 20x1,5 | Rd. 28 x 2 | 325,0 | -30 | 100 | 4 |
| SKFS 08 HS 3 | 3 | 8 | S | 12 | M 20x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 10 HS 3 | 3 | 10 | S | 14 | M 22x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 10 HS 4 | 4 | 10 | S | 14 | M 22x1,5 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 13 HS 3 | 3 | 12 | S | 16 | M 24x1,5 | Rd. 36 x 2 | 300,0 | -30 | 100 | 4 |
| SKFS 13 HS 4 | 4 | 12 | S | 16 | M 24x1,5 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 16 HS 4 | 4 | 16 | S | 20 | M 30x2 | Rd. 42 x 2 | 250,0 | -30 | 100 | 4 |
| SKFS 16 HS 5 | 5 | 16 | S | 20 | M 30x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 20 HS 5 | 5 | 19 | S | 25 | M 36x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 25 HS 5 | 5 | 25 | S | 30 | M 42x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 25 HS 6 | 6 | 25 | S | 30 | M 42x2 | Rd. 70 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 32 HS 5 | 5 | 31 | S | 38 | M 52x2 | Rd. 48 x 3 | 250,0 | -30 | 100 | 4 |
| SKFS 32 HS 6 | 6 | 31 | S | 38 | M 52x2 | Rd. 70 x 3 | 250,0 | -30 | 100 | 4 |



SKFS HL / SKFS HS

Screw coupling (fixed)

Accessories

| | |
|-------------|-------------------------|
| SKF ZUBS | Dust protection for SKF |
| SKF ZUBS AL | Cap |

Spare parts

| | |
|----------------|-------------------------------|
| SKF BREMSRING | Brake ring for screw coupling |
| SKF STUETZRING | Support ring for SKF |
| SKF ORING | O-ring for SKF |