# SKL HJ

Screw coupling (loose)

## Properties

| | |
|---|---|
| **Application** | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| **Connection 1** | UN/UNF external threads |
| **Sealing form 1** | 74° outer cone |
| **Residual pressure:** | Coupling under residual pressure is possible |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Description

Screw couplings are designed for high pressures and pressure pulses.
It is recommended to combine only couplings same manufacturer.

## Additional information

The robust construction makes them ideal for use in harsh conditions.
If fitted correctly, the screw sleeve completely covers the brake ring.

## Item

| Identification | Size | DN* | Connecting thread | Coupling thread | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) | SF coup.* |
|---|---|---|---|---|---|---|---|---|
| **SKL 10 HJ 2** | 2 | 10 | UNF 9/16" -18 | Rd. 28 x 2 | 350,0 | -25 | 100 | 4 |
| **SKL 13 HJ 2** | 2 | 12 | UNF 3/4" -16 | Rd. 28 x 2 | 350,0 | -25 | 100 | 4 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

| | |
|---|---|
| **SKL ZUBS** | Dust protection for SKL |
| **SKL ZUBS AL** | Dust protector |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*