

### Properties

|                    |   |
|--------------------|---|
| Application        | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Connection 1       | NPT external threads  |
| Sealing form 1     | thread seal   |
| Residual pressure: | Coupling under residual pressure is possible  |
| compatible with    | Pioneer   |
| Additional feature | with ball valve   |
| Material           | Steel   |
| Surface            | electro galvanised  |



### Ordering information

Other pressure and temperature figures available on request.

### Additional information

The robust construction makes them ideal for use in harsh conditions.

#### Item

| Identification         | DN* | Connecting thread | Operating pressure<br>(bar) | Mineral oil temp. min.<br>(°C) | Mineral oil temp. max.<br>(°C) | SF coup.* |
|------------------------|-----|-------------------|-----------------------------|--------------------------------|--------------------------------|-----------|
| <b>SKL 06 HN SP</b>    | 6   | NPT 1/4" -18      | 700,0                       | -25                            | 110                            | 3         |
| <b>SKL 10 HN 06 SP</b> | 10  | NPT 1/4" -18      | 700,0                       | -25                            | 125                            | 3         |
| <b>SKL 10 HN SP</b>    | 10  | NPT 3/8" -18      | 700,0                       | -30                            | 80                             | 3         |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

### Accessories

**SKL ZUBS SP** Dust protection for SKL...SP