# SKL HN SP KE

Screw coupling (loose)

## Properties

| | |
|---|---|
| **Application** | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| **Connection 1** | NPT external threads |
| **Sealing form 1** | thread seal |
| **Residual pressure:** | Coupling under residual pressure is possible |
| **compatible with** | Pioneer |
| **Additional feature** | with plug valve |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Description

Screw couplings are designed for high pressures and pressure pulses.

## Additional information

The robust construction makes them ideal for use in harsh conditions.

## Item

| Identification | DN* | Connecting thread | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) | SF coup.* |
|---|---|---|---|---|---|---|
| **SKL 06 HN SP KE** | 6 | NPT 1/4" -18 | 1050,0 | -25 | 125 | 3 |
| **SKL 10 HN SP KE** | 10 | NPT 3/8" -18 | 1000,0 | -25 | 125 | 3 |

BD = Working pressure – SF gek. = Safety factor coupled

## Accessories

| | |
|---|---|
| **SKF ZUBS SP** | Dust protection for SKF...SP |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*