

SKL IM AE

Screw coupling (loose)

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	metric cylindrical inner thread
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Residual pressure:	Coupling under residual pressure is possible
compatible with	Aeroquip
Material	Steel
Surface	electro galvanised



Description

Screw couplings are designed for high pressures and pressure pulses.

Ordering information

Other pressure and temperature figures available on request.

Additional information

The robust construction makes them ideal for use in harsh conditions.

Item								
Identification	DN*	Connecting thread	Coupling thread	Operating pressure (bar)	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)	SF coup.*	
SKL 13 IM AE	12	M 22x1,5	Rd. 35 x 2	350,0	-30	100	4	
SKL 16 IM AE	16	M 26x1,5	Rd. 42 x 2	350,0	-30	100	-	
SKL 20 IM AE	19	M 30x1,5	Rd. 54 x 3	350,0	-30	100	4	
SKL 25 IM AE	25	M 38x1,5	Rd. 64 x 3	350,0	-40	150	-	

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKL ZUBS AE	Dust protection for SKL...AE
-------------	------------------------------