

**Properties**

Application	Agricultural technology
Connection 1	UN/UNF inner thread
Sealing form 1	for screw-in pins with shape F
compatible with	John Deere
Material	Steel
Surface	electro galvanised



**Note**

Interchangeable with couplings to ISO 7241-1, Series A.

**Description**

Plug-in couplings allow quick coupling.

<b>Item</b>							
Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 13 IJ 3 JD</b>	12	UNF 3/4" -16	3	250,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

**Accessories**

<b>SKM ZUBS 3 CB</b>	Dust protection coupling sleeve, SKM..
<b>SKM ZUB 3 12</b>	Quick release clip with spring
<b>SKM ZUB 3 11</b>	Quick release clip with dust protection
<b>SKM ZUBS</b>	Dust protection coupling sleeve, SKM..
<b>SKM ZUBS 3 C</b>	Dust protection coupling sleeve, SKM..
<b>SKM ZUB BLINDSTECKER</b>	Dummy connector for plug-in coupling sleeve

**Spare parts**

<b>SKM STUETZRING</b>	Support ring for SKM
<b>SKM ORING</b>	O-ring for SKM