SKM IJ JD

Plug-in coupling sleeve

Properties

Application	Agricultural technology
Connection 1	UN/UNF inner thread
Sealing form 1	for screw-in pins with shape F
compatible with	John Deere
Material	Steel
Surface	electro galvanised



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Item

Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 13 IJ 3 JD	12	UNF 3/4" -16	3	250,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS 3 CB	Dust protection coupling sleeve, SKM..
SKM ZUB 3 12	Quick release clip with spring
SKM ZUB 3 11	Quick release clip with dust protection
SKM ZUBS	Dust protection coupling sleeve, SKM..
SKM ZUBS 3 C	Dust protection coupling sleeve, SKM..
SKM ZUB BLINDSTECKER	Dummy connector for plug-in coupling sleeve

Spare parts

SKM STUETZRING	Support ring for SKM
SKM ORING	O-ring for SKM

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.