

SKM IN AE

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	NPT internal thread
Sealing form 1	thread seal
compatible with	Aeroquip
Material	Steel
Surface	electro galvanised



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item						
Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 06 IN AE	6	NPT 1/4" -18	210,0	4	-25	100
SKM 10 IN AE	10	NPT 3/8" -18	210,0	4	-25	100
SKM 13 IN AE	12	NPT 1/2" -14	210,0	4	-25	100
SKM 20 IN AE	19	NPT 3/4" -14	210,0	4	-25	100
SKM 25 IN AE	25	NPT 1" -11,5	200,0	4	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS AE	Dust protection coupling sleeve, SKM..AE
--------------------	--

Spare parts

SKM STUETZRING AE	Support ring for SKM...AE
SKM ORING AE	O-ring for SKM...AE