SKM IN F

Plug-in coupling sleeve

HANSA-FLEX

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	NPT internal thread
Sealing form 1	thread seal
compatible with	Faster
Material	Steel
Surface	electro galvanised



Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
The safety retaining ring prevents unwanted uncoupling.
Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 10 IN F	10	NPT 3/8" -18	250,0	4	-25	100
SKM 10 IN 13 F	10	NPT 1/2" -14	250,0	4	-25	100
SKM 20 IN 25 F	19	NPT 1" -11,5	250,0	4	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS FS	Dust protection coupling sleeve, SKM..FS

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.