

### Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	NPT internal thread
<b>Sealing form 1</b>	thread seal
<b>compatible with</b>	Faster
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.  
 For a high flow with minimal pressure loss.  
 The safety retaining ring prevents unwanted uncoupling.  
 Suitable for use in environmentally sensitive areas.

### Ordering information

Other pressure and temperature figures available on request.

Item						
Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 10 IN F</b>	10	NPT 3/8" -18	250,0	4	-25	100
<b>SKM 10 IN 13 F</b>	10	NPT 1/2" -14	250,0	4	-25	100
<b>SKM 20 IN 25 F</b>	19	NPT 1" -11,5	250,0	4	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

### Accessories

<b>SKM ZUBS FS</b>	Dust protection coupling sleeve, SKM..FS
--------------------	--