


**Properties**

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Design</b>	Snap-tite series H
<b>Connection 1</b>	NPT internal thread
<b>Sealing form 1</b>	thread seal
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



**Description**

Plug-in couplings allow quick coupling.

**Item**

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 06 IN SN H</b>	6	NPT 1/4" -18	450,0	2	-40	90
<b>SKM 10 IN SN H</b>	10	NPT 3/8" -18	310,0	2	-40	90
<b>SKM 13 IN SN H</b>	12	NPT 1/2" -14	280,0	2	-40	90
<b>SKM 20 IN SN H</b>	19	NPT 3/4" -14	245,0	2	-40	90
<b>SKM 25 IN SN H</b>	25	NPT 1" -11,5	140,0	2	-40	90
<b>SKM 32 IN SN H</b>	31	NPT 1.1/4" -11,5	125,0	2	-40	90
<b>SKM 40 IN SN H</b>	38	NPT 1.1/2" -11,5	105,0	2	-40	90
<b>SKM 65 IN SN H</b>	65	NPT 2.1/2" -8	70,0	2	-40	90
<b>SKM 75 IN SN H</b>	76	NPT 3" -8	55,0	2	-40	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

**Accessories**

**SKM ZUBS SN H** Dust protection coupling sleeve, SKM..SN H