SKM IN SP

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	NPT internal thread
Sealing form 1	thread seal
compatible with	Pioneer
Additional feature	with ball valve
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 06 IN SP	6	NPT 1/4" -18	200,0	4	-25	110
SKM 10 IN SP	10	NPT 3/8" -18	200,0	4	-25	110
SKM 13 IN SP	12	NPT 1/2" -14	200,0	4	-25	125
SKM 13 IN 20 SP	12	NPT 3/4" -14	200,0	-	-40	110
SKM 20 IN SP	19	NPT 3/4" -14	200,0	4	-25	110
SKM 25 IN SP	25	NPT 1" -11,5	200,0	4	-25	110

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS SP	Dust protection coupling sleeve, SKM..SP

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.