

**Properties**

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	NPT internal thread
<b>Sealing form 1</b>	thread seal
<b>compatible with</b>	Pioneer
<b>Additional feature</b>	with ball valve
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



**Description**

Plug-in couplings allow quick coupling.

**Ordering information**

Other pressure and temperature figures available on request.

**Item**

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 06 IN SP</b>	6	NPT 1/4" -18	200,0	4	-25	110
<b>SKM 10 IN SP</b>	10	NPT 3/8" -18	200,0	4	-25	110
<b>SKM 13 IN SP</b>	12	NPT 1/2" -14	200,0	4	-25	125
<b>SKM 13 IN 20 SP</b>	12	NPT 3/4" -14	200,0	-	-40	110
<b>SKM 20 IN SP</b>	19	NPT 3/4" -14	200,0	4	-25	110
<b>SKM 25 IN SP</b>	25	NPT 1" -11,5	200,0	4	-25	110

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

**Accessories**

**SKM ZUBS SP** Dust protection coupling sleeve, SKM..SP