

# SKM IN SP KE

## Plug-in coupling sleeve

### Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	NPT internal thread
<b>Sealing form 1</b>	thread seal
<b>compatible with</b>	Pioneer
<b>Additional feature</b>	with plug valve
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Description

Plug-in couplings allow quick coupling.

### Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 06 IN SP KE</b>	6	NPT 1/4" -18	350,0	4	-25	125
<b>SKM 10 IN SP KE</b>	10	NPT 3/8" -18	300,0	4	-25	125
<b>SKM 13 IN SP KE</b>	12	NPT 1/2" -14	300,0	4	-25	125
<b>SKM 25 IN SP KE</b>	25	NPT 1" -11,5	230,0	4	-25	125

BD = Working pressure – SF gek. = Safety factor coupled

### Accessories

<b>SKM ZUBS SP</b>	Dust protection coupling sleeve, SKM..SP
--------------------	--