

SKM IN SP KE

Plug-in coupling sleeve

Properties

| | |
|---------------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Connection 1 | NPT internal thread |
| Sealing form 1 | thread seal |
| compatible with | Pioneer |
| Additional feature | with plug valve |
| Material | Steel |
| Surface | electro galvanised |



Description

Plug-in couplings allow quick coupling.

Item

| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|------------------------|-----|-------------------|-----------------------------|-----------|--------------------------------|--------------------------------|
| SKM 06 IN SP KE | 6 | NPT 1/4" -18 | 350,0 | 4 | -25 | 125 |
| SKM 10 IN SP KE | 10 | NPT 3/8" -18 | 300,0 | 4 | -25 | 125 |
| SKM 13 IN SP KE | 12 | NPT 1/2" -14 | 300,0 | 4 | -25 | 125 |
| SKM 25 IN SP KE | 25 | NPT 1" -11,5 | 230,0 | 4 | -25 | 125 |

BD = Working pressure – SF gek. = Safety factor coupled

Accessories

| | |
|--------------------|--|
| SKM ZUBS SP | Dust protection coupling sleeve, SKM..SP |
|--------------------|--|