

Properties			
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.		
Connection 1	BSP cylindrical internal threads		
Sealing form 1	for screw-in pins with shapes A, B and if necessary E		
Standard	complies with ISO 7241 series A		
compatible with	Aeroquip		
Material	Steel		
Surface	electro galvanised		



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item						
Identification	DN*	Connecting thread	Operating pressure	SF coup.*	Mineral oil temp. min.	Mineral oil temp. max.
SKM 10 IR AE	10	G 3/8" -19	210,0	4	-25	100
SKM 13 IR AE	12	G 1/2" -14	210,0	4	-25	100
SKM 20 IR AE	19	G 3/4" -14	250,0	4	-25	100
SKM 25 IR AE	25	G 1" -11	200,0	4	-25	100

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled

Acc	200	COP	-
$\Delta U = 0$		301	

SKM ZUBS AE Dust protection coupling sleeve, SKM..AE

Spare parts		
SKM STUETZRING AE	Support ring for SKMAE	
SKM ORING AE	O-ring for SKMAE	