SKM IR AE

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Standard	complies with ISO 7241 series A
compatible with	Aeroquip
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 10 IR AE	10	G 3/8" -19	210,0	4	-25	100
SKM 13 IR AE	12	G 1/2" -14	210,0	4	-25	100
SKM 20 IR AE	19	G 3/4" -14	250,0	4	-25	100
SKM 25 IR AE	25	G 1" -11	200,0	4	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS AE	Dust protection coupling sleeve, SKM..AE

Spare parts

SKM STUETZRING AE	Support ring for SKM...AE
SKM ORING AE	O-ring for SKM...AE

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.