# SKM IR HC

Plug-in coupling sleeve

## Properties

| | |
|---|---|
| **Application** | Emergency tools, clamping tools, presses etc. |
| **Connection 1** | BSP cylindrical internal threads |
| **Sealing form 1** | for screw-in pins with shapes A, B and if necessary E |
| **Scope of supply** | with dust protection |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Description

Plug-in coupling for quick coupling in the extreme pressure range.
Coupling and uncoupling with minimal drips.

## Item

| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|---|---|---|---|---|---|---|
| **SKM 04 IR HC** | 4 | G 1/8" -28 | 1000,0 | 2,5 | -30 | 100 |
| **SKM 06 IR HC** | 6 | G 1/4" -19 | 1000,0 | 2,5 | -30 | 100 |
| **SKM 10 IR HC** | 10 | G 3/8" -19 | 1000,0 | 2,5 | -30 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*