

# SKM IR MC

Plug-in coupling sleeve for medium pressure

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>Scope of supply</b>	with dust protection
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Description

The small size saves space in use.

For a high flow with minimal pressure loss.

Plug-in couplings allow quick coupling.

## Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 06 IR MC</b>	6	G 1/4" -19	250,0	4	-30	100
<b>SKM 10 IR MC</b>	10	G 3/8" -19	250,0	4	-30	100
<b>SKM 13 IR MC</b>	12	G 1/2" -14	250,0	4	-30	100
<b>SKM 20 IR MC</b>	19	G 3/4" -14	320,0	3	-30	100
<b>SKM 25 IR MC</b>	25	G 1" -11	320,0	3	-30	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled