

| Properties      |   |
|-----------------|---|
| Application     | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Connection 1    | BSP cylindrical internal threads  |
| Sealing form 1  | for screw-in pins with shapes A, B and if necessary E                                       |
| Scope of supply | with dust protection  |
| Material        | Steel   |
| Surface         | electro galvanised  |



## **Description**

The small size saves space in use.

For a high flow with minimal pressure loss.

Plug-in couplings allow quick coupling.

| Item           |     |                   |                          |           |                        |                        |  |
|----------------|-----|-------------------|--------------------------|-----------|------------------------|------------------------|--|
| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. | Mineral oil temp. max. |  |
| SKM 06 IR MC   | 6   | G 1/4" -19        | 250,0                    | 4         | -30                    | 100                    |  |
| SKM 10 IR MC   | 10  | G 3/8" -19        | 250,0                    | 4         | -30                    | 100                    |  |
| SKM 13 IR MC   | 12  | G 1/2" -14        | 250,0                    | 4         | -30                    | 100                    |  |
| SKM 20 IR MC   | 19  | G 3/4" -14        | 320,0                    | 3         | -30                    | 100                    |  |
| SKM 25 IR MC   | 25  | G 1" -11          | 320,0                    | 3         | -30                    | 100                    |  |

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled