# SKM IR MC

Plug-in coupling sleeve for medium pressure

## Properties

| | |
|---|---|
| **Application** | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| **Connection 1** | BSP cylindrical internal threads |
| **Sealing form 1** | for screw-in pins with shapes A, B and if necessary E |
| **Scope of supply** | with dust protection |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Description

The small size saves space in use.
For a high flow with minimal pressure loss.
Plug-in couplings allow quick coupling.

## Item

| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|---|---|---|---|---|---|---|
| **SKM 06 IR MC** | 6 | G 1/4" -19 | 250,0 | 4 | -30 | 100 |
| **SKM 10 IR MC** | 10 | G 3/8" -19 | 250,0 | 4 | -30 | 100 |
| **SKM 13 IR MC** | 12 | G 1/2" -14 | 250,0 | 4 | -30 | 100 |
| **SKM 20 IR MC** | 19 | G 3/4" -14 | 320,0 | 3 | -30 | 100 |
| **SKM 25 IR MC** | 25 | G 1" -11 | 320,0 | 3 | -30 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*