SKM IR SN71-3

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Material	Steel
Surface	electro galvanised



Description

Used for high pressures and severe pressure pulses.
Single handed operation when coupling (if the counter piece is fitted securely).
Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 06 IR SN71-3	6	G 1/4" -19	690,0	2	-40	90
SKM 10 IR SN71-3	10	G 3/8" -19	690,0	2	-40	90
SKM 13 IR SN71-3	12	G 1/2" -14	690,0	2	-40	90
SKM 20 IR SN71-3	19	G 3/4" -14	520,0	2	-40	90
SKM 25 IR SN71-3	25	G 1" -11	520,0	2	-40	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS SN71	Dust protection coupling sleeve, SKM..SN 71

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.