

# SKM IR SN72

## Plug-in coupling sleeve

### Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Design</b>	Snap-tite series 72
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>Standard</b>	ISO 7241-1 Series B
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Description

Plug-in couplings allow quick coupling.

### Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 04 IR SN72</b>	5	G 1/8" -28	500,0	4	-40	90
<b>SKM 06 IR SN72</b>	6	G 1/4" -19	250,0	4	-25	90
<b>SKM 10 IR SN72</b>	10	G 3/8" -19	250,0	4	-25	90
<b>SKM 13 IR SN72</b>	12	G 1/2" -14	250,0	4	-25	90
<b>SKM 20 IR SN72</b>	19	G 3/4" -14	250,0	4	-25	90
<b>SKM 25 IR SN72</b>	25	G 1" -11	200,0	4	-25	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

### Product versions

**SKM IR SN72 VA** Plug-in coupling sleeve, Stainless steel

### Accessories

**SKM ZUBS SN72** Dust protection coupling sleeve, SKM..SN 72