

SKM IR SN72

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	Snap-tite series 72
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Standard	ISO 7241-1 Series B
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 04 IR SN72	5	G 1/8" -28	500,0	4	-40	90
SKM 06 IR SN72	6	G 1/4" -19	250,0	4	-25	90
SKM 10 IR SN72	10	G 3/8" -19	250,0	4	-25	90
SKM 13 IR SN72	12	G 1/2" -14	250,0	4	-25	90
SKM 20 IR SN72	19	G 3/4" -14	250,0	4	-25	90
SKM 25 IR SN72	25	G 1" -11	200,0	4	-25	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKM IR SN72 VA Plug-in coupling sleeve, Stainless steel

Accessories

SKM ZUBS SN72 Dust protection coupling sleeve, SKM..SN 72