

Properties

| | |
|--------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Connection 1 | BSP cylindrical internal threads |
| Sealing form 1 | for screw-in pins with shapes A, B and if necessary E |
| compatible with | Pioneer |
| Additional feature | with plug valve |
| Material | Steel |
| Surface | electro galvanised |



Description

Plug-in couplings allow quick coupling.

Item

| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|------------------------|-----|-------------------|-----------------------------|-----------|--------------------------------|--------------------------------|
| SKM 06 IR SP KE | 6 | G 1/4" -19 | 350,0 | 4 | -25 | 125 |
| SKM 10 IR SP KE | 10 | G 3/8" -19 | 300,0 | 4 | -25 | 125 |
| SKM 13 IR SP KE | 12 | G 1/2" -14 | 300,0 | 4 | -25 | 125 |
| SKM 20 IR SP KE | 19 | G 3/4" -14 | 250,0 | 4 | -25 | 125 |

BD = Working pressure – SF gek. = Safety factor coupled

Accessories

| | |
|--------------------|--|
| SKM ZUBS SP | Dust protection coupling sleeve, SKM..SP |
|--------------------|--|