SKM IR T

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
compatible with	Tema



Description

Plug-in couplings allow quick coupling.
For a high flow with minimal pressure loss.
Increased security due to double O-ring seal.
The safety retaining ring prevents unwanted uncoupling.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 06 IR T	6	G 1/4" -19	450,0	2,5	-30	100
SKM 10 IR T	10	G 3/8" -19	350,0	3,0	-30	100
SKM 13 IR T	12	G 1/2" -14	300,0	3,0	-30	100
SKM 20 IR T	19	G 3/4" -14	280,0	2,5	-30	100
SKM 25 IR T	25	G 1" -11	250,0	3,5	-30	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKM ZUBS T	Dust protection coupling sleeve, SKM..T

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.