SKS HL / SKS HS

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Standard	complies with ISO 7241 series A
Material	Steel
Surface	electro galvanised



Note

nominal width 10, size 3 also available in ED version

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Series	for external pipe Ø (mm)	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 04 HL 2	4	L	6	M 12x1,5	2	250,0	4	-30	100
SKS 06 HL 2	6	L	8	M 14x1,5	2	250,0	4	-30	100
SKS 06 HL 3	6	L	8	M 14x1,5	3	225,0	4	-30	100
SKS 08 HL 2	8	L	10	M 16x1,5	2	250,0	4	-30	100
SKS 08 HL 3	8	L	10	M 16x1,5	3	225,0	4	-30	100
SKS 10 HL 3	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 3 ED	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 4	10	L	12	M 18x1,5	4	225,0	4	-30	100
SKS 13 HL 3	12	L	15	M 22x1,5	3	225,0	4	-30	100
SKS 13 HL 4	12	L	15	M 22x1,5	4	225,0	4	-30	100
SKS 16 HL 3	16	L	18	M 26x1,5	3	225,0	4	-30	100
SKS 16 HL 4	16	L	18	M 26x1,5	4	225,0	4	-30	100
SKS 16 HL 5	16	L	18	M 26x1,5	5	225,0	4	-30	100
SKS 20 HL 4	19	L	22	M 30x2	4	225,0	4	-30	100
SKS 20 HL 5	19	L	22	M 30x2	5	225,0	4	-30	100
SKS 25 HL 5	25	L	28	M 36x2	5	225,0	4	-30	100
SKS 04 HS 2	4	S	8	M 16x1,5	2	250,0	4	-30	100
SKS 06 HS 1	6	S	10	M 18x1,5	1	300,0	4	-25	100
SKS 06 HS 2	6	S	10	M 18x1,5	2	250,0	4	-30	100
SKS 06 HS 3	6	S	10	M 18x1,5	3	225,0	4	-30	100
SKS 08 HS 2	8	S	12	M 20x1,5	2	250,0	4	-30	100
SKS 08 HS 3	8	S	12	M 20x1,5	3	225,0	4	-30	100
SKS 10 HS 3	10	S	14	M 22x1,5	3	225,0	4	-30	100
SKS 10 HS 4	10	S	14	M 22x1,5	4	225,0	4	-30	100
SKS 13 HS 3	12	S	16	M 24x1,5	3	225,0	4	-30	100
SKS 13 HS 4	12	S	16	M 24x1,5	4	225,0	4	-30	100
SKS 16 HS 3	16	S	20	M 30x2	3	225,0	4	-25	100
SKS 16 HS 4	16	S	20	M 30x2	4	225,0	4	-30	100
SKS 16 HS 5	16	S	20	M 30x2	5	225,0	4	-30	100
SKS 20 HS 5	19	S	25	M 36x2	5	225,0	4	-30	100
SKS 25 HS 5	25	S	30	M 42x2	5	225,0	4	-30	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS	Dust protection coupling connector, SKS..
SKS ZUB 3	Connector clip for coupling connector SKS..3

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.