SKS HL FS
Plug-in coupling connector

Properties

suitable for	Plug-in coupling connector SKS...FS
Design	flat sealing
Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
compatible with	Stucchi
Material	Steel
Surface	electro galvanised



Note

With standard threaded connections in determining the operating pressure of the maximum rated pressure is taken into account.
nominal width 10, size 2 also available in ED version
Interchangeable with couplings to ISO 16028.

Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Series	for external pipe Ø (mm)	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 08 HL 2 FS	8	L	10	M 16x1,5	2	350,0	4,0	-20	100
SKS 10 HL 2 FS	10	L	12	M 18x1,5	2	350,0	4,0	-20	100
SKS 10 HL 2 FS ED	10	L	12	M 18x1,5	2	350,0	4,0	-20	100
SKS 10 HL 3 FS	10	L	12	M 18x1,5	3	350,0	4,0	-20	100
SKS 13 HL 2 FS	12	L	15	M 22x1,5	2	350,0	4,0	-20	100
SKS 13 HL 3 FS	12	L	15	M 22x1,5	3	350,0	4,0	-20	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled – BD = Working pressure

Accessories

SKS ZUBS FS	Dust protection coupling connector, SKS..FS

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.