SKS HL UDK / SKS HS UDK

Plug-in coupling connector

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Residual pressure:	Coupling under residual pressure is possible
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Item

Identification	DN*	Series	for external pipe Ø (mm)	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 HL 3 UDK	6	L	8	M 14x1,5	3	225,0	4	-25	125
SKS 08 HL 3 UDK	8	L	10	M 16x1,5	3	225,0	4	-25	125
SKS 10 HL 3 UDK	10	L	12	M 18x1,5	3	225,0	4	-25	125
SKS 13 HL 3 UDK	12	L	15	M 22x1,5	3	225,0	4	-25	125
SKS 16 HL 3 UDK	16	L	18	M 26x1,5	3	225,0	4	-25	125
SKS 06 HS 3 UDK	6	S	10	M 18x1,5	3	225,0	4	-25	125
SKS 08 HS 3 UDK	8	S	12	M 20x1,5	3	225,0	4	-25	125
SKS 10 HS 3 UDK	10	S	14	M 22x1,5	3	225,0	4	-25	125
SKS 13 HS 3 UDK	12	S	16	M 24x1,5	3	225,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS	Dust protection coupling connector, SKS..

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.