

Properties				
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.			
Connection 1	UN/UNF inner thread			
Sealing form 1	for screw-in pins with shape F			
compatible with	Stucchi			
Material	Steel			
Surface	electro galvanised			



Note

Interchangeable with couplings to ISO 16028.

Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.

For a high flow with minimal pressure loss.

Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item							
Identification	DN*	Connecting thread	Size	Operating pressure	SF coup.*	Mineral oil temp. min.	Mineral oil temp. max.
SKS 10 IJ 1 FS	10	UNF 9/16" -18	1	350,0	4	-20	100
SKS 13 IJ 2 FS	12	UNF 3/4" -16	2	350,0	4	-20	100
SKS 16 IJ 3 FS	16	UNF 7/8" -14	3	350,0	4	-20	100
SKS 20 IJ 3 FS	19	UN 1.1/16" -12	3	350,0	4	-20	100

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled

Accessories	
SKS ZUBS FS	Dust protection coupling connector, SKSFS