SKS IJ FS

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	UN/UNF inner thread
Sealing form 1	for screw-in pins with shape F
compatible with	Stucchi
Material	Steel
Surface	electro galvanised



Note

Interchangeable with couplings to ISO 16028.

Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 10 IJ 1 FS	10	UNF 9/16" -18	1	350,0	4	-20	100
SKS 13 IJ 2 FS	12	UNF 3/4" -16	2	350,0	4	-20	100
SKS 16 IJ 3 FS	16	UNF 7/8" -14	3	350,0	4	-20	100
SKS 20 IJ 3 FS	19	UN 1.1/16" -12	3	350,0	4	-20	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS FS	Dust protection coupling connector, SKS..FS

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.