

## Properties

|                        |   |
|------------------------|---|
| <b>Application</b>     | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| <b>Connection 1</b>    | metric cylindrical inner thread   |
| <b>Sealing form 1</b>  | for screw-in pins with shapes A, B and if necessary E                                       |
| <b>compatible with</b> | Aeroquip  |
| <b>Material</b>        | Steel   |
| <b>Surface</b>         | electro galvanised  |



## Note

Interchangeable with couplings to ISO 7241-1, Series A.

## Description

Plug-in couplings allow quick coupling.

## Ordering information

Other pressure and temperature figures available on request.

| Item | Identification      | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|------|---------------------|-----|-------------------|--------------------------|-----------|-----------------------------|-----------------------------|
|      | <b>SKS 10 IM AE</b> | 10  | M 18x1,5          | 250,0                    | 4         | -25                         | 100                         |
|      | <b>SKS 13 IM AE</b> | 12  | M 22x1,5          | 210,0                    | 4         | -25                         | 100                         |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

**SKS ZUBS AE** Dust protection coupling connector, SKS..AE