

Properties

| | |
|---------------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Connection 1 | NPT internal thread |
| Sealing form 1 | thread seal |
| compatible with | Aeroquip |
| Additional feature | ISO 7241-1 A |
| Material | Steel |
| Surface | electro galvanised |



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

| Item | | | | | | |
|----------------|-----|-------------------|-----------------------------|-----------|--------------------------------|--------------------------------|
| Identification | DN* | Connecting thread | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
| SKS 06 IN AE | 6 | NPT 1/4" -18 | 210,0 | 4 | -25 | 100 |
| SKS 10 IN AE | 10 | NPT 3/8" -18 | 210,0 | 4 | -25 | 100 |
| SKS 13 IN AE | 12 | NPT 1/2" -14 | 210,0 | 4 | -25 | 100 |
| SKS 20 IN AE | 19 | NPT 3/4" -14 | 210,0 | 4 | -25 | 100 |
| SKS 25 IN AE | 25 | NPT 1" -11,5 | 200,0 | 4 | -25 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

| | |
|--------------------|---|
| SKS ZUBS AE | Dust protection coupling connector, SKS..AE |
|--------------------|---|