SKS IN AE

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	NPT internal thread
Sealing form 1	thread seal
compatible with	Aeroquip
Additional feature	ISO 7241-1 A
Material	Steel
Surface	electro galvanised



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IN AE	6	NPT 1/4" -18	210,0	4	-25	100
SKS 10 IN AE	10	NPT 3/8" -18	210,0	4	-25	100
SKS 13 IN AE	12	NPT 1/2" -14	210,0	4	-25	100
SKS 20 IN AE	19	NPT 3/4" -14	210,0	4	-25	100
SKS 25 IN AE	25	NPT 1" -11,5	200,0	4	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS AE	Dust protection coupling connector, SKS..AE

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.