

SKS IN SN H

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	Snap-tite series H
Connection 1	NPT internal thread
Sealing form 1	thread seal
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Item						
Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IN SN H	6	NPT 1/4" -18	450,0	2	-40	90
SKS 10 IN SN H	10	NPT 3/8" -18	310,0	2	-40	90
SKS 13 IN SN H	12	NPT 1/2" -14	280,0	2	-40	90
SKS 20 IN SN H	19	NPT 3/4" -14	245,0	2	-40	90
SKS 25 IN SN H	25	NPT 1" -11,5	140,0	2	-40	90
SKS 32 IN SN H	31	NPT 1.1/4" -11,5	125,0	2	-40	90
SKS 40 IN SN H	38	NPT 1.1/2" -11,5	105,0	2	-40	90
SKS 50 IN SN H	51	NPT 2" -11,5	105,0	2	-40	90
SKS 65 IN SN H	65	NPT 2.1/2" -8	70,0	2	-40	90
SKS 75 IN SN H	76	NPT 3" -8	55,0	2	-40	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS SN H	Dust protection coupling connector, SKS..SN H
----------------------	---