

# SKS IN SP

Plug-in coupling connector

**HANSA FLEX**

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	NPT internal thread
<b>Sealing form 1</b>	thread seal
<b>compatible with</b>	Pioneer
<b>Additional feature</b>	with ball valve
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Description

Plug-in couplings allow quick coupling.

## Ordering information

Other pressure and temperature figures available on request.

## Item

Identification	DN*	Connecting thread	L (mm)	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IN SP	6	NPT 1/4" -18	35,3	200,0	4	-25	110
SKS 10 IN SP	10	NPT 3/8" -18	38,0	200,0	4	-25	110
SKS 13 IN SP	12	NPT 1/2" -14	51,4	200,0	4	-25	125
SKS 13 IN 20 SP	12	NPT 3/4" -14	54,4	200,0	-	-40	110
SKS 20 IN SP	19	NPT 3/4" -14	46,0	200,0	4	-25	110
SKS 25 IN SP	25	NPT 1" -11,5	64,3	200,0	4	-25	110

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

SKS ZUBS SP Dust protection coupling connector, SKS..SP