SKS IR AE

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
compatible with	Aeroquip
Material	Steel
Surface	electro galvanised



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 10 IR AE	10	G 3/8" -19	210,0	4,0	-25	100
SKS 13 IR AE	12	G 1/2" -14	210,0	4,0	-25	100
SKS 20 IR AE	19	G 3/4" -14	250,0	3,5	-25	100
SKS 25 IR AE	25	G 1" -11	200,0	4,0	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS AE	Dust protection coupling connector, SKS..AE

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.