

Properties						
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.					
Connection 1	BSP cylindrical internal threads					
Sealing form 1	for screw-in pins with shapes A, B and if necessary E					
compatible with	Aeroquip					
Material	Steel					
Surface	electro galvanised					



Note

Interchangeable with couplings to ISO 7241-1, Series A.

Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min.	Mineral oil temp. max.
SKS 10 IR AE	10	G 3/8" -19	210,0	4,0	-25	100
SKS 13 IR AE	12	G 1/2" -14	210,0	4,0	-25	100
SKS 20 IR AE	19	G 3/4" -14	250,0	3,5	-25	100
SKS 25 IR AE	25	G 1" -11	200,0	4,0	-25	100

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled

Δ	CC	20	er	۱ri	Δ0
$\boldsymbol{\mathcal{L}}$	-	CC	J	/I I	00

SKS ZUBS AE Dust protection coupling connector, SKS..AE