

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>compatible with</b>	Aeroquip
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Note

Interchangeable with couplings to ISO 7241-1, Series A.

## Description

Plug-in couplings allow quick coupling.

## Ordering information

Other pressure and temperature figures available on request.

Item						
Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 10 IR AE	10	G 3/8" -19	210,0	4,0	-25	100
SKS 13 IR AE	12	G 1/2" -14	210,0	4,0	-25	100
SKS 20 IR AE	19	G 3/4" -14	250,0	3,5	-25	100
SKS 25 IR AE	25	G 1" -11	200,0	4,0	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

<b>SKS ZUBS AE</b>	Dust protection coupling connector, SKS..AE
--------------------	---