

SKS IR FS

Plug-in coupling connector

Properties

| | |
|------------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Design | flat sealing |
| Connection 1 | BSP cylindrical internal threads |
| Sealing form 1 | for screw-in pins with shapes A, B and if necessary E |
| compatible with | Stucchi |
| Material | Steel |
| Surface | electro galvanised |



Note

Interchangeable with couplings to ISO 16028.

Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
 For a high flow with minimal pressure loss.
 Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

| Identification | DN* | Connecting thread | Size | Operating pressure (bar) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|-----------------------|-----|-------------------|------|--------------------------|-----------|-----------------------------|-----------------------------|
| SKS 06 IR 1 FS | 6 | G 1/4" -19 | 1 | 400,0 | 4 | -30 | 100 |
| SKS 10 IR 2 FS | 10 | G 3/8" -19 | 2 | 350,0 | 4 | -30 | 100 |
| SKS 13 IR 2 FS | 12 | G 1/2" -14 | 2 | 350,0 | 4 | -30 | 100 |
| SKS 13 IR 3 FS | 12 | G 1/2" -14 | 3 | 350,0 | 4 | -30 | 100 |
| SKS 20 IR 3 FS | 19 | G 3/4" -14 | 3 | 350,0 | 4 | -30 | 100 |
| SKS 20 IR 4 FS | 19 | G 3/4" -14 | 4 | 350,0 | 4 | -30 | 100 |
| SKS 25 IR 5 FS | 25 | G 1" -11 | 5 | 350,0 | 4 | -30 | 100 |
| SKS 32 IR 6 FS | 31 | G 1.1/4" -11 | 6 | 300,0 | 4 | -20 | 100 |
| SKS 40 IR 7 FS | 38 | G 1.1/2" -11 | 7 | 200,0 | 4 | -20 | 100 |
| SKS 50 IR 8 FS | 51 | G 2" -11 | 8 | 200,0 | 4 | -20 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKS IR FS VA Plug-in coupling connector, Stainless steel

Accessories

SKS ZUBS FS Dust protection coupling connector, SKS..FS