SKS IR FS
Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	flat sealing
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
compatible with	Stucchi
Material	Steel
Surface	electro galvanised



Note
Interchangeable with couplings to ISO 16028.

Description
Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
Suitable for use in environmentally sensitive areas.

Ordering information
Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IR 1 FS	6	G 1/4" -19	1	400,0	4	-30	100
SKS 10 IR 2 FS	10	G 3/8" -19	2	350,0	4	-30	100
SKS 13 IR 2 FS	12	G 1/2" -14	2	350,0	4	-30	100
SKS 13 IR 3 FS	12	G 1/2" -14	3	350,0	4	-30	100
SKS 20 IR 3 FS	19	G 3/4" -14	3	350,0	4	-30	100
SKS 20 IR 4 FS	19	G 3/4" -14	4	350,0	4	-30	100
SKS 25 IR 5 FS	25	G 1" -11	5	350,0	4	-30	100
SKS 32 IR 6 FS	31	G 1.1/4" -11	6	300,0	4	-20	100
SKS 40 IR 7 FS	38	G 1.1/2" -11	7	200,0	4	-20	100
SKS 50 IR 8 FS	51	G 2" -11	8	200,0	4	-20	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKS IR FS VA	Plug-in coupling connector, Stainless steel

Accessories

SKS ZUBS FS	Dust protection coupling connector, SKS..FS

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.