SKS IR SN71-3

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Material	Steel
Surface	electro galvanised



Description

Used for high pressures and severe pressure pulses.
Single handed operation when coupling (if the counter piece is fitted securely).
Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IR SN71-3	6	G 1/4" -19	690,0	2	-40	90
SKS 10 IR SN71-3	10	G 3/8" -19	690,0	2	-40	90
SKS 13 IR SN71-3	12	G 1/2" -14	690,0	2	-40	90
SKS 20 IR SN71-3	19	G 3/4" -14	520,0	2	-40	90
SKS 25 IR SN71-3	25	G 1" -11	520,0	2	-40	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS SN71	Dust protection coupling connector, SKS..SN 71

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.