SKS IR SN72

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	Snap-tite series 72
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Additional feature	ISO 7241-1 Series B
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 04 IR SN72	5	G 1/8" -28	500,0	4	-40	90
SKS 06 IR SN72	6	G 1/4" -19	250,0	4	-25	90
SKS 10 IR SN72	10	G 3/8" -19	250,0	4	-25	90
SKS 13 IR SN72	12	G 1/2" -14	250,0	4	-25	90
SKS 20 IR SN72	19	G 3/4" -14	250,0	4	-25	90
SKS 25 IR SN72	25	G 1" -11	200,0	4	-25	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKS IR SN72 VA	Plug-in coupling connector, Stainless steel

Accessories

SKS ZUBS SN72	Dust protection coupling connector, SKS..SN 72

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.