

SKS IR SN72

Plug-in coupling connector



Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	Snap-tite series 72
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Additional feature	ISO 7241-1 Series B
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 04 IR SN72	5	G 1/8" -28	500,0	4	-40	90
SKS 06 IR SN72	6	G 1/4" -19	250,0	4	-25	90
SKS 10 IR SN72	10	G 3/8" -19	250,0	4	-25	90
SKS 13 IR SN72	12	G 1/2" -14	250,0	4	-25	90
SKS 20 IR SN72	19	G 3/4" -14	250,0	4	-25	90
SKS 25 IR SN72	25	G 1" -11	200,0	4	-25	90

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKS IR SN72 VA Plug-in coupling connector, Stainless steel

Accessories

SKS ZUBS SN72 Dust protection coupling connector, SKS..SN 72