

# SKS IR SN H VA

Stainless steel plug-in coupling connector

**HANSA FLEX**

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Design</b>	Snap-tite series H
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>Material</b>	Stainless steel



## Description

Plug-in couplings allow quick coupling.

## Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKS 06 IR SN H VA</b>	6	G 1/4" -19	345,0	2	-29	190
<b>SKS 10 IR SN H VA</b>	10	G 3/8" -19	280,0	2	-29	190
<b>SKS 13 IR SN H VA</b>	12	G 1/2" -14	260,0	2	-29	190
<b>SKS 20 IR SN H VA</b>	19	G 3/4" -14	140,0	2	-29	190
<b>SKS 25 IR SN H VA</b>	25	G 1" -11	140,0	2	-29	190

BD = Working pressure – SF gek. = Safety factor coupled

## Accessories

<b>SKS ZUBS SN H</b>	Dust protection coupling connector, SKS..SN H
----------------------	---